



Negujemo prirodu



TEHNIČKE KARAKTERISTIKE

ROTACIONI RASPRSKIVAČ I-20

Hunter® INOVATORI U NAVODNJAVANJU

Rotacioni rasprskivači velikih performansi sa velikom razvršnošću i efikasnosti je pogodan za sve površine. Sa 22 vrste dizni, radijusom od 4,9 do 14 m i 6 tipova tela, I-20 je pravi izbor.

KARAKTERISTIKE I PREDNOSTI

- **Široki asortiman izmenljivih dizni**
sa 22 izmenljive dizne I podesivim uglom od 50° do 360° stepeni moguće je rešiti i zadovoljiti svaki zadatak zalivanja, a različite boje omogućuju brzu identifikaciju
- **Ugrađeni, ekstra izdržljivi gumeni poklopac**
štiti glavu od mehaničkih oštećenja i prljavštine
- **Lako servisiranje glave rasprskivača**
brz i jednostavan prilaz delovima i mehanizmu pri podešavanju ili servisiranju
- **Zatvoreno kućište rasprskivača**
apsolutna zaštita od prljavštine
- **Dokazano izdržljiv unutrašnji mehanizam**
samo potkrepljuje pojam pouzdanosti ovog modela
- **Snažna povratna opruga**
izdignuta glava rasprskivača po prestanku rada pod bilo kojim uslovima vraća se u uvučeni položaj
- **Mehanizam za brzu proveru ugla**
- **Vodeno podmazivanje mehanizma**
- **Automatski povrat ugla**
- **Delimičan i pun krug zalivanja u jednom modelu**

DIMENZIJE

Vidljiva površina glave: Ø 4,5 cm

3/4" unutrašnji navoj: NPT

RADNI PARAMETRI

- **Propusna moć (protok vode):**
do 0,07 do 3,23 m³/čas; od 1,2 do 53,8 l/min
- **Preporučeni pritisak:**
od 1,4 do 7 bara; od 140 do 700 kPa
- **Količina padavina:** približno 10 mm/čas
- **Putanja dizni:**
standardni – 25 stepeni
nizak ugao – 13 stepeni

MODELI

• **Modeli sa plastičnom glavom:**
I-20-00, I-20-04, I-20-06 i I-20-12

• **Modeli sa metalnom glavom:**
I-20-04, I-20-06



I-20-00

- žbunje
- ukupna visina 20 cm



I-20-04

- izlazi 10 cm
- ukupna visina 19 cm



I-20-06

- izlazi 15 cm,
- ukupna visina 25 cm



I-20-12

- izlazi 30 cm
- ukupna visina 43 cm

ROTACIONI RASPRSKIVAČ I-20

Hunter®

INOVATORI U NAVODNJAVANJU

**PODACI O UČINKU I-20
PLAVIH STANDARDNIH DIZNI**

Dizna	Pritisak Bar kPa	Radijus m	Protok m ³ /h l/min	Vodeni talog ■ mm/h ▲	
1.5 ●	1.7 170	8.8	0.27 4.5	7	8
	2.0 200	9.1	0.29 4.8	7	8
	2.5 250	9.4	0.32 5.4	7	8
	3.0 300	9.8	0.35 5.9	7	9
	3.5 350	9.8	0.38 6.4	8	9
	4.0 400	9.8	0.41 6.8	9	10
2.0 ●	1.7 170	10.1	0.32 5.4	6	7
	2.0 200	10.1	0.35 5.8	7	8
	2.5 250	10.1	0.39 6.5	8	9
	3.0 300	10.4	0.43 7.2	8	9
	3.5 350	10.4	0.47 7.8	9	10
	4.0 400	10.4	0.50 8.3	9	11
2.5 ● Blue	1.7 170	10.1	0.39 6.6	8	9
	2.0 200	10.4	0.43 7.1	8	9
	2.5 250	10.7	0.48 8.0	8	10
	3.0 300	10.7	0.54 8.9	9	11
	3.5 350	10.7	0.58 9.7	10	12
	4.0 400	10.7	0.62 10.4	11	13
3.0 ● Blue	1.7 170	10.7	0.50 8.4	9	10
	2.0 200	10.7	0.54 9.1	10	11
	2.5 250	11.0	0.61 10.2	10	12
	3.0 300	11.6	0.68 11.4	10	12
	3.5 350	11.9	0.74 12.3	10	12
	4.0 400	11.9	0.79 13.2	11	13
4.0 ● Blue	1.7 170	11.3	0.68 11.3	11	12
	2.0 200	11.6	0.73 12.2	11	13
	2.5 250	11.9	0.81 13.6	12	13
	3.0 300	12.2	0.90 15.0	12	14
	3.5 350	12.2	0.97 16.2	13	15
	4.0 400	12.5	1.04 17.3	13	15
5.0 ● Blue	1.7 170	11.3	0.84 14.0	13	15
	2.0 200	11.6	0.91 15.2	14	16
	2.5 250	11.9	1.02 17.1	15	17
	3.0 300	12.8	1.14 19.0	14	16
	3.5 350	12.8	1.24 20.6	15	17
	4.0 400	12.8	1.32 22.1	16	19
6.0 ● Blue	1.7 170	11.6	1.01 16.8	15	17
	2.0 200	11.9	1.09 18.2	15	18
	2.5 250	12.2	1.22 20.4	16	19
	3.0 300	13.1	1.36 22.7	16	18
	3.5 350	13.1	1.47 24.5	17	20
	4.0 400	13.4	1.57 26.2	18	20
8.0 ● Blue	1.7 170	11.3	1.35 22.5	21	25
	2.0 200	11.9	1.46 24.3	21	24
	2.5 250	12.5	1.63 27.2	21	24
	3.0 300	13.4	1.81 30.2	20	23
	3.5 350	13.7	1.95 32.6	21	24
	4.0 400	14.0	2.09 34.8	21	25
4.5 450	14.0	2.22 36.9	23	26	

**PODACI O UČINKU I-20
SIVIH DIZNI SA NISKIM UGLOM**

Dizna	Pritisak Bar kPa	Radijus m	Protok m ³ /h l/min	Vodeni talog ■ mm/h ▲	
2.0 ● la	1.7 170	7.3	0.33 5.6	12	14
	2.0 200	7.6	0.36 6.0	12	14
	2.5 250	7.9	0.40 6.7	13	15
	3.0 300	8.2	0.45 7.4	13	15
	3.5 350	8.5	0.48 8.0	13	15
	4.0 400	8.8	0.52 8.6	13	15
2.5 ● la	1.7 170	7.9	0.44 7.3	14	16
	2.0 200	8.2	0.47 7.9	14	16
	2.5 250	8.8	0.53 8.8	14	16
	3.0 300	9.4	0.59 9.8	13	15
	3.5 350	10.1	0.64 10.6	13	15
	4.0 400	10.4	0.68 11.3	13	15
3.5 ● la Grey	1.7 170	8.5	0.58 9.7	16	18
	2.0 200	8.8	0.62 10.3	16	18
	2.5 250	9.1	0.68 11.4	16	19
	3.0 300	10.1	0.75 12.5	15	17
	3.5 350	10.7	0.80 13.3	14	16
	4.0 400	11.0	0.85 14.1	14	16
4.0 ● la Grey	1.7 170	8.2	0.71 11.8	21	24
	2.0 200	8.8	0.76 12.7	19	23
	2.5 250	9.1	0.84 14.1	20	23
	3.0 300	10.1	0.93 15.5	18	21
	3.5 350	10.7	1.00 16.6	18	20
	4.0 400	11.0	1.06 17.6	18	20
4.5 450	11.3	1.12 18.6	18	20	

Napomena

Količine vodenog taloga su prikazane za ugao zalivanja od 180°. Za stvaranje vodenog taloga pri punom krugu zalivanja računajte sa dupliranim vrednostima.

**DIZNE**

PLAVA: standardna
SIVA: niski ugao



Alati za
podešavanje dizni

ROTACIONI RASPRSKIVAČ I-20

Hunter®

INOVATORI U NAVODNJAVANJU

**PODACI O UČINKU I-20
TAMNO ZELENIH DIZNI SA VELIKIM PROTOKOM**

Dizna		Pritisak		Radijus m	Protok		Vodeni talog	
		Bar	kPa		m ³ /h	l/min	mm/h	▲
10	●	1.7	170	10.7	1.48	24.6	26	30
		2.0	200	11.9	1.60	26.7	23	26
		2.5	250	12.5	1.80	30.0	23	27
		3.0	300	12.8	2.01	33.5	25	28
		3.5	350	13.1	2.18	36.3	25	29
		4.0	400	13.7	2.34	39.0	25	29
	4.5	450	14.0	2.49	41.5	25	29	
13	●	1.7	170	11.0	1.91	31.9	32	37
		2.0	200	12.2	2.08	34.6	28	32
		2.5	250	12.8	2.34	38.9	29	33
		3.0	300	13.1	2.61	43.4	30	35
		3.5	350	13.4	2.83	47.1	31	36
		4.0	400	13.7	3.03	50.5	32	37
	4.5	450	14.0	3.23	53.8	33	38	
6.0 la	●	1.7	170	9.1	0.86	14.3	21	24
		2.0	200	9.4	0.94	15.6	21	24
		2.5	250	10.1	1.07	17.8	21	24
		3.0	300	10.7	1.20	20.0	21	24
		3.5	350	11.3	1.31	21.9	21	24
		4.0	400	11.6	1.42	23.6	21	24
	4.5	450	11.9	1.52	25.3	21	25	
8.0 la	●	1.7	170	10.1	1.17	19.5	23	27
		2.0	200	10.7	1.28	21.3	22	26
		2.5	250	11.3	1.44	24.0	23	26
		3.0	300	11.6	1.61	26.9	24	28
		3.5	350	11.9	1.76	29.3	25	29
		4.0	400	12.5	1.89	31.5	24	28
	4.5	450	12.5	2.01	33.6	26	30	

Napomena

Količine vodenog taloga su prikazane za ugao zalivanja od 180°. Za stvaranje vodenog taloga pri punom krugu zalivanja računajte sa dupliranim vrednostima.


**PODACI O UČINKU I-20
CRNIH DIZNI SA MALIM RADIJUSOM**

Dizna		Pritisak		Radijus m	Protok		Vodeni talog	
		Bar	kPa		m ³ /h	l/min	mm/h	▲
.50 sR	●	1.7	170	4.9	0.07	1.2	6	7
		2.0	200	5.2	0.08	1.3	6	7
		2.5	250	5.2	0.09	1.5	7	8
		3.0	300	5.2	0.10	1.7	8	9
		3.5	350	5.5	0.12	1.9	8	9
		4.0	400	5.5	0.13	2.1	8	10
	4.5	450	5.5	0.14	2.3	9	10	
1.0 sR	●	1.7	170	4.9	0.16	2.7	14	16
		2.0	200	5.2	0.17	2.9	13	15
		2.5	250	5.2	0.19	3.2	14	17
		3.0	300	5.2	0.21	3.6	16	18
		3.5	350	5.5	0.23	3.8	15	18
		4.0	400	5.5	0.25	4.1	16	19
	4.5	450	5.5	0.26	4.3	17	20	
2.0 sR	●	1.7	170	4.9	0.28	4.7	24	27
		2.0	200	5.2	0.31	5.2	23	27
		2.5	250	5.2	0.36	6.0	27	31
		3.0	300	5.2	0.41	6.9	31	35
		3.5	350	5.5	0.45	7.6	30	35
		4.0	400	5.5	0.49	8.2	33	38
	4.5	450	5.5	0.53	8.9	35	41	
.75 sR	●	1.7	170	6.7	0.12	2.0	5	6
		2.0	200	7.0	0.13	2.2	5	6
		2.5	250	7.0	0.15	2.4	6	7
		3.0	300	7.3	0.16	2.7	6	7
		3.5	350	7.6	0.17	2.9	6	7
		4.0	400	7.6	0.19	3.1	6	7
	4.5	450	7.6	0.20	3.3	7	8	
1.5 sR	●	1.7	170	6.7	0.23	3.8	10	12
		2.0	200	7.0	0.25	4.1	10	12
		2.5	250	7.0	0.28	4.6	11	13
		3.0	300	7.3	0.31	5.2	12	13
		3.5	350	7.6	0.34	5.6	12	13
		4.0	400	7.6	0.36	6.0	12	14
	4.5	450	7.6	0.39	6.4	13	15	
3.0 sR	●	1.7	170	6.7	0.53	8.9	24	27
		2.0	200	7.0	0.56	9.3	23	26
		2.5	250	7.0	0.60	10.0	24	28
		3.0	300	7.3	0.64	10.7	24	28
		3.5	350	7.6	0.67	11.2	23	27
		4.0	400	7.6	0.70	11.7	24	28
	4.5	450	7.6	0.73	12.1	25	29	

Napomena

Količine vodenog taloga su prikazane za ugao zalivanja od 180°. Za stvaranje vodenog taloga pri punom krugu zalivanja računajte sa dupliranim vrednostima.

DIZNE



TAMNO ZELENE:
veliki protok



CRNE:
mali radijus

SKALA GARDEN DOO – Horgoški Put 110, 24413 Palić, Srbija – PIB: 103604815

Telefon: +381 (0)24 602-980 • Fax: +381 (0)24 602-981 • Email: office@skalagarden.com • www.skalagarden.com
Mat. br.: 08827176 • Reg. br.: 23608827176 • Šifra del.: 2573 • Tek. račun: 265-2410310004133-15, RAIFFEISEN BANK AD